



AT1200 TOW | Electric Tow Tugger

The AT1200 TOW electric tug is perfect for safely towing loads where weight transfer is not possible, up to 26,000 lb. The tug is self-weighted and compact, providing excellent traction for effortless load towing whilst attaching to any load with a draw bar, towing eye or ball hitch fitting. It can be used inside or outside, including on slopes and less than perfect surfaces.



KeyBenefits


1 year full guarantee


- FEA tested steel chassis
- Internal weight packs

• Optimised size, puncture -proof wheels

ProductDimensions







SafetyFeatures

See our website for full technical details



Automatic cut off when tiller arm returns to vertical



Anti-crush button



Emergency stop button



Warning horn

MaxLoadWeight

See our website for full technical details





*"Maximum load weight" is only a recommendation that we arrive at by estimating rolling resistance. Your environment and wheel type may affect this figure which is why we carry out a detailed technical evaluation on every project. All of our calculations include a "safe work load" factor to ensure safe operation in all circumstances.

TechnicalData

See our website for full technical details

I al	_	4	:4		_4		_	
Ia	е	nt	ш	IC	ลา	ш	D	n

Product code	AT1200 TOW			
Recommended load weight - Castors ¹	26500 lbs			
Recommended load weight - Rails ²	48000 kg			
Machine weight including battery	1350 kg			
Drive type	Electric AC			
Parking brake	Electromagnetic			
Drive wheel type	Superelastic Solid Rubber			
Drive motor power	2 x 2.0 kW			
Controller type	AC			
Variable machine speed	0-3.7 mph			
Ingress Protection	IP44			

Battery options

Battery pack - sealed - 204Ah 24V - Interchangeable

Battery pack - sealed - 179 Ah 24V - Interchangable

Battery pack - lithium - 158 Ah 24V - fixed

Additional equipment

Option - flashing safety light and motion bleeper

Option - two speed selector switch

Option - fifth wheel

Option - wireless control handset

Option - battery protection system

Option - Lithium battery

Male coupling options

Coupling - male - pin

Coupling - male - height adjustable tow ball - 50mm

Coupling - male - height adjustable box

Coupling - male - adjustable towing arm

Coupling - male - height adjustable tow ball - 50mm

Coupling - male - height adjustable box

Female coupling options

Coupling - female - box

TechnicalData

See our website for full technical details

1 - Recommended load weight - Castors

AT1200 TOW Maximum Starting Load on Castors (Pulling only)

2 - Recommended load weight - Rails

AT1200 TOW Maximum Starting Load on Rails (pulling only)

To arrange a demonstration, or for further information about our electric tug material handling solutions, please contact us

MasterMover Inc, 8041-J Arrowridge Boulevard, Charlotte, NC 28273, , USA

Telephone Sales: 980-263-2210 Email: sales@mastermover.com

Fax: Website: www.mastermover.com



AboutUs

Located in Charlotte, North Carolina, MasterMover is a business success story with customers all over the world.

Our products are relied upon by market leading organisations and global brands across a broad cross-section of industries including Aerospace, Automotive, Pharmaceutical, Retail and Healthcare.

